



Matters needing attention in production

General Specifications	
Wire specifications	28/24AWG
Contact quantity	4
Temperature range	-25℃~+80℃
Withstand voltage	≥DC300V
Insulation resistance	≥10MΩ DC300V

Pin Assignment		
P1	Wire Color	P2
1	Red	1
2	White	2
3	Green	3
4	Black	4
Shell	Shield Braid	Shell

深圳市正成电气有限公司  
受控文件

6	USB 2.0 AM Three piece white Core Shell Nickel Plated(A180400-1737)	pc	1
5	UL2725 1P*28AWG+2C*24AWG+AL+D+B, jacket black PVC OD:4.5(1P: white&green; 2C: red, black) (A150101-0046)	pc	1
4	E13 threaded HDMI connecting nut (formed) (A130202-0269)	pc	1
3	USB waterproof gasket Φ18.6-12-4.4-1.5 (A140100-0086)	pc	1
2	overmolding PVC black (A170900-0001)	pc	2
1	USB 2.0 A/M white rubber core short body shell nickel plated (A180400-1736)	pc	1
No.	Specification	Unit	Q'ty

GENERAL TOLERANCE (UNLESS SPECIFIED) ≤10 ±0.1 <10~≤20 ±0.2 <20~≤50 ±0.5 Angle ±3'	DWN		
	CHK		
	APVD		
 THIRD ANGLE	UNIT MM	REV A	TITLE E13T-MU2-MWA/NWA-2PV-S
	SIZE A4	SHEET 1 OF 1	PART NO 2CA2-USB20-TKL-AA-2000 DRAWING NO C130505-00097

Statement: Please confirm and return the drawings within 2 working days. If the drawings are not returned after the expiration date, the default is that you have been confirmed to be qualified.

Business confirmation

Customer	DWN NO	DATE	DWN	APVD
P/N		2024-03-30	Junming. Hu	
Product Name		UNIT: mm	Size: A4	 RoHS